

1280 Enterprise Series

Programmable Color Touchscreen Weight Indicator/Controller



Standard Features

- Seven-inch, 800 x 480 pixel, graphical color display that adjusts for ambient light conditions
- Twelve-inch, 1280 x 800 pixel, graphical color display that adjusts for ambient light conditions
- Highly customizable graphical user interface
- Three different enclosure types: universal with tilt stand, panel mount and wall mount
- Resistive color touchscreen that can be used with gloves
- On-screen keyboard available during entry mode or use an external keyboard
- Multi-language operation and text entry
- Keypad for scale operations, numeric entry and navigation
- More than 150 built-in functions for programming
- Customize applications and data tables with iRite™ software
- Built-in web server for remote access, systems integration and data monitoring
- Up to eight scales supporting five scale types:
 - Analog load cell scales
 - Total scales
 - Serial scales
 - Program scales
 - iQube2 scales
- Multi-range/interval weighing functions
- Eight digital I/O for control and pulse count
- 100 setpoints, 18 configurable setpoint types
- 22 soft keys with 10 user-defined
- Two RS-232 and RS-485 serial ports
- USB, Ethernet TCP/IP, Wi-Fi Direct(r) and Bluetooth® ports

Options

- Six option slots that support:
 - A/D scale channels
 - Analog Input/Thermocouple
 - Digital input and outputs
 - Analog outputs
 - Serial ports
 - Four channel dry-contact relay
 - Various protocol interfaces

Approvals*



Measurement
Canada
Approved



* Touch-only units
pending approvals

Specifications

Power:

AC voltages: 100-240VAC; 50-60 Hz
DC voltages: 11-30VDC
Consumption: 60W

Excitation Voltage:

10 ± 0.5VDC
16 x 350Ω or 16 x 700Ω load cells per A/D card

Analog Signal Input Range:

-60 mV to 60 mV

Analog Signal Sensitivity:

0.3 μV/graduation minimum at 7.5 Hz–120 Hz
1.0 μV/graduation recommended

A/D Sample Rate:

7.5 to 960 Hz, software selectable

Resolution:

Internal: 8 million counts
Display: 9,999,999

System Linearity

± 0.01% full scale

Digital I/O:

Eight I/O channels on CPU board; optional serial ports:
24-channel I/O expansion boards available

Communication Ports:

Port 1 & 2: Full duplex RS-232 with CTS/RTS, RS-422/485
Baud Rate: 1200 to 115200
Port 3: USB 2.0 Device (Micro)
Port 4: Bluetooth® SPP 2.1+EDR, Standards 4Mbaud
USB Host: (2) Type A Connectors max 500 mA
Ethernet: Wired 10/100 Auto-MDX
Ethernet: Wireless 802.11 b/g/n 2.4GHz

Onboard:

Selectable filters: Three stage, Adaptive or Damping
Embedded Linux® OS
8 GB eMMC (system use)
1 GB DDR3 RAM
460 MB onboard database (SQLite) storage
Up to 32 GB micro SD card (sold separately)

Display:

Seven-inch, 800 x 480 pixel, graphical color TFT display 500 or 1000 NIT
Twelve-inch, 1280 x 800 pixel, graphical color TFT display 1500 NIT

Keys/Buttons:

22-key membrane panel, tactile buttons, on-screen keyboard for text and numeric entry, USB port for flash drive, keyboard and printer

Temperature Range

Certified: 14°F to 104°F (-10°C to 40°C)
Operating: -4°F to 131°F (-20°C to 55°C)

Weight:

Universal enclosure: 11 lb (4.9 kg)
Panel mount enclosure: 8 lb (3.6 kg)
Wall mount enclosure: 23 lb (10.4 kg)
Panel mount 7 in touch-only enclosure: 7 lb (3.1 kg)
Panel mount 12 in touch-only enclosure: 10 lb (4.5 kg)

Rating/Material:

IP66 stainless steel wall enclosure
IP69K stainless steel universal and panel mount door

Warranty:

Two-year limited warranty

EMC Immunity:

EN 50082 Part 2 IEC EN 61000-4-2, 3, 4, 5, 6, 8, and 11

Approvals:

NTEP CC 15-00/Class III/III 10,000d
Measurement Canada AM-5980C,
Class III/III HD 10,000d
OIML R76/2006-NL1-16.04 Class III/III 10,000d
EU Test Certificate TC8596
UL/cUL Listed (universal)
UL/cUL Recognized (panel mount)
CE Marked

1280 Enterprise Series

Programmable Color Touchscreen Weight Indicator/Controller

INDICATORS / CONTROLLERS

www.ricelake.com | Phone: 800-472-6703

RICE LAKE

527



7-inch model with keypad




7-inch touch-only model




12-inch touch-only model


Numeric Keypad Models:



1280-2



1280-3




1280-4

Universal (1280-2) Dimensions	
A 10.86 in (276 mm)	B 6.22 in (158 mm)
C 9.24 in (235 mm)	D 4.97 in (126 mm)
E 9.00 in (229 mm)	F 12.50 in (318 mm)
G 5.25 in (133 mm)	


Wall Mount (1280-3) Dimensions	
A 14.92 in (379 mm)	B 11 in (279 mm)
C 18.22 in (463 mm)	D 18.84 in (479 mm)
E 19.64 in (499 mm)	F 14.20 in (361 mm)
G 8.08 in (205 mm)	

Panel Mount (1280-4) Dimensions	
A 9.00 in (229 mm)	B 9.00 in (229 mm)
C 0.58 in (15 mm)	D 5.34 in (136 mm)
E 0.32 in (8 mm)	

Touch-only Models:



1280-5



1280-6

7-inch Touch-only (1280-5) Dimensions	
A 9.00 in (229 mm)	B 6.22 in (158 mm)


12-inch Touch-only (1280-6) Dimensions	
A 14.00 in (356 mm)	B 10 in (254 mm)

1280 Enterprise Series

Programmable Color Touchscreen Weight Indicator/Controller

Generate a 1280 Enterprise Series Model Reference Code

This reference number can be used at time of ordering.



Part Number

Part #	Reference #	Description	Power	Display	Option Installed	Price
Universal Enclosure with 500 NIT Display (1280-2)						
171427†	1111BAAAAA	1280 Universal	115 VAC	500 NIT	Single Scale Card	Consult
171441††	1131BAAAAA	1280 Universal	100-240 VAC	500 NIT	Single Scale Card	Consult
171662†	1111CAAAAA	1280 Universal	115 VAC	500 NIT	Dual Scale Card	Consult
172188††	1131CAAAAA	1280 Universal	100-240 VAC	500 NIT	Dual Scale Card	Consult
Panel Mount Enclosure with 500 NIT Display (1280-4)						
171663	21-3BAAAAA	1280 Panel Mount	100-240 VAC	500 NIT	Single Scale Card	Consult
172186	21-3CAAAAA	1280 Panel Mount	100-240 VAC	500 NIT	Dual Scale Card	Consult
Wall Mount Enclosure with 500 NIT Display (1280-3)						
173673†	3143BAAAAA	1280 Wall Mount	115 VAC	500 NIT	Single Scale Card	Consult
174143††	3153BAAAAA	1280 Wall Mount	100-240 VAC	500 NIT	Single Scale Card	Consult
174144†	3143CAAAAA	1280 Wall Mount	115 VAC	500 NIT	Dual Scale Card	Consult
174145††	3153CAAAAA	1280 Wall Mount	100-240 VAC	500 NIT	Dual Scale Card	Consult
Wall Mount Enclosure with 1000 NIT Display (1280-3)						
172184†	3144BAAAAA	1280 Wall Mount	115 VAC	1000 NIT	Single Scale Card	Consult
172185††	3154BAAAAA	1280 Wall Mount	100-240 VAC	1000 NIT	Single Scale Card	Consult
173806†	3144CAAAAA	1280 Wall Mount	115 VAC	1000 NIT	Dual Scale Card	Consult
172187††	3154CAAAAA	1280 Wall Mount	100-240 VAC	1000 NIT	Dual Scale Card	Consult
Touch-only 7 inch with 500 NIT Display (1280-5)						
186618	41-3BAAAAA	1280 Touch-only 7 in	100-240 VAC	500 NIT	Single Scale Card	Consult
Touch-only 12 inch with 1500 NIT Display (1280-6)						
186465	51-5BAAAAA	1280 Touch-only 12 in	100-240 VAC	1500 NIT	Single Scale Card	Consult

† NEMA 5-15 plug †† CEE 7/7 plug (Euro)

1280 Enterprise Series

Programmable Color Touchscreen Weight Indicator/Controller

Single A/D Scale



Excitation Voltage:
10 VDC bi-polar, 4 or 6 wire sensing
16 x 350 ohms per channel
Analog Input Signal:
-10 to +40 mV

Part #	Description	Price
164085	Single scale A/D	Consult
163407	Board only	Consult
166957	A/D sealing kit	Consult

Dual A/D Scale



Excitation Voltage:
10 VDC bi-polar, 4 or 6 wire sensing
8 x 350 ohms per channel
Analog Input Signal:
-10 to +40 mV

Part #	Description	Price
164683	Dual scale A/D	Consult
160760	Board only	Consult
166957	A/D sealing kit	Consult

Digital I/O



24 channels, configurable as inputs or outputs
Inputs: 5 VDC max, active low; Outputs: 20 mA max per channel, active low; 5 VDC source available: 500 mA max

Part #	Description	Price
164684	Digital I/O	Consult
160761	Board only	Consult

For 24 I/O ribbon cable required.

Dual Serial Channel



Two-channel, full duplex RS-232 with CTS/RTS, RS-485 or RS-422, 1200-115200 baud

Part #	Description	Price
164685	Dual serial channel	Consult
162930	Board only	Consult

Single Analog Out



16 bit, voltage output 0-10 VDC, current output 0-20mA, 4-20mA

Part #	Description	Price
165366	Single analog out	Consult
164704	Board only	Consult

Dual Analog Out



16 bit, voltage output 0-10 VDC, current output 0-20mA, 4-20mA

Part #	Description	Price
164686	Dual analog out	Consult
162931	Board only	Consult

Relay Card



Relay four-dry contact, max current 3A @ 30 VDC, 3A @250VAC

Part #	Description	Price
164689	Relay card	Consult
164974	Board only	Consult

Analog Input / Thermocouple



Analog Input Signal:
±10VDC, ±100mV, 0-20mA
Thermocouple Types:
E, J, K, N, T

Part #	Description	Price
164687	Dual analog input	Consult
162932	Board only	Consult

Data Exchange with PLC/DCS Systems

EtherNet/IP



Part #	Description	Price
165792	EtherNet/IP	Consult
152357	EtherNet/IP Module only	Consult
164756	Host board only	Consult

DeviceNet



Part #	Description	Price
165793	DeviceNet	Consult
152360	DeviceNet module only	Consult
164756	Host board only	Consult

Profinet



Part #	Description	Price
165794	Profinet	Consult
152355	Profinet module only	Consult
164756	Host board only	Consult

Modbus TCP



Part #	Description	Price
165796	Modbus TCP	Consult
152359	Modbus TCP module only	Consult
164756	Host board only	Consult

Profibus DP



Part #	Description	Price
165795	Profibus DP	Consult
152358	Profibus module only	Consult
164756	Host board only	Consult

EtherCAT



Part #	Description	Price
179533	EtherCAT	Consult
163295	Module, EtherCAT	Consult
164756	Host board only	Consult

PowerLink



Part #	Description	Price
182319	PowerLink	Consult
183004	PowerLink module only	Consult
164756	Host board only	Consult

1280 Enterprise Series


Programmable Color Touchscreen Weight Indicator/Controller

Grayhill Relays and Racks



Part #	Description	Price
52332	Two-channel input relay, 2.5-28 VDC	Consult
52318	Two-channel input relay, 120 VAC	Consult
52319	Two-channel input relay, 240 VAC	Consult
52331	Two-channel input relay, 10-32 VDC	Consult
52316	Two-channel output relay, 120-140 VAC at 2 amp	Consult
52317	Two-channel output relay, 240-280 VAC at 7 amp	Consult
71376	Two-channel output relay, 3-60 VDC at 1 amp	Consult
71377	Two-channel output relay, 0-200 VDC/VAC at 1.5A/10W (dry contact)	Consult
84698	Two-channel output relay, inductive load, 120-140 VAC at 2A	Consult
84699	Two-channel output relay, inductive load, 240-280 VAC at 2A	Consult
52312	Eight-channel relay rack, panel mount and wall mount, requires 50-Pin flat or round ribbon cable - 4 slots	Consult
52314	16-channel relay rack, panel mount and wall mount, requires 50-Pin flat or round ribbon cable - 8 slots	Consult
52315	24-channel relay rack, panel mount and wall mount, requires 50-Pin flat or round ribbon cable - 12 slots	Consult
170008	Cable, 60-Pin flat ribbon w 50-Pin adapter, 24 in length	Consult
170009	Cable, 60-Pin round w 50-Pin adapter, 60 in length	Consult
170736	Cable, 60-Pin round w/ cord grip and 50-Pin adapter	Consult

Options


Part #	Description	Price
Manuals and Software		
77925	Revolution scale software	Consult
166046	Manual, Operation	Consult
167659	Manual, Technical	Consult
167660	CD, 1280 Documents	Consult
164939	8 GB Micro SD card with SD and USB adapter	Consult
173046	USB flash drive, 1 GB	Consult




Unsealed Connectors



Sealed Connector



Sealed Receptacle



Options

Part #	Description	Price
Primary Component Parts		
163400	7 in 500 NIT display	Consult
163399	7 in 1000 NIT display	Consult
182992	12 in 1500 NIT display	Consult
160757*	CPU board assembly	Consult
160758	Back Plane board assembly	Consult
162693	AC power supply board	Consult
162694	DC power supply board	Consult
164121	Overlay, keypad, for panel & wall mount	Consult
164120	Overlay, touchscreen, for panel & wall mount	Consult
161731	Overlay, keypad, for universal	Consult
161730	Overlay, touchscreen, for universal	Consult
178498	Overlay, touchscreen, for 7 in touch-only panel mount	Consult
176126	Overlay, touchscreen, for 12 in touch-only panel mount	Consult

The fan plate (PN 169350) will need to be updated if replacing CPU version A, B or C

Options/Accessories

Part #	Description	Connector Type				Price
		Sealed		Unsealed		
USB Cables (Note: Cables have a plug)						
		A	B	A	B	
152434	Unsealed connectors USB-A to USB micro A, 2 m cable			X		Consult
79074	Unsealed connectors USB-A to USB-B, 2 m cable			X	X	Consult
124700	Sealed connectors, USB-A to USB-B, 3 m IP68 cable	X	X			Consult
126477	Sealed connector USB-A to unsealed connector USB-A, 3 m IP68 cable	X		X		Consult
124701	Sealed connector USB-A to unsealed connector USB-B, 3 m IP68 cable	X			X	Consult
124702	Sealed connector USB-B to unsealed connector USB-A, 3 m IP68 cable		X	X		Consult
USB Receptacles (Note: Receptacles have a socket)						
176790	Sealed receptacle USB-A for panel mount, 0.75 m cable	X				Consult
126476	Sealed receptacle USB-A for wall mount, 0.5 m cable	X		X		Consult
172735	Sealed receptacle USB-A for universal, 0.25 m cable	X		X		Consult
124694	Cover for sealed receptacles					Consult
124689	Cover for flash driver mounts on sealed receptacle					Consult
Ethernet Cables						
		Sealed		Unsealed		
72697	Unsealed Ethernet, RJ45 to RJ45, 2 m cable				X	Consult
124706	Sealed to sealed Ethernet 3 m cable	X				Consult
124707	Sealed to unsealed Ethernet 3 m cable	X		X		Consult
Ethernet Receptacles						
		Sealed		Unsealed		
176789	Sealed receptacle Ethernet RJ-45, 0.75 m cable	X				Consult
172734	Sealed receptacle Ethernet RJ-45, 0.5 m cable	X				Consult
126353	Sealed receptacle Ethernet RJ-45, 0.25 m cable	X				Consult